




WR-10 Antenna Test & Measurement Frequency Extension System 75-110 GHz: AET/AER-10-0001

Farran's AET-10-0001 and AER-10-0001 frequency extenders are a dedicated Test & Measurement solution for antenna performance verification in WR-10 (75 – 110 GHz).

The system comprises of the transmitter (AET) and receiver (AER) units that enable antenna radiation pattern, gain and phase polarisation measurements in the near- and far-field.

Key Facts:

- Dynamic range > 110 dB.
- Exceptional amplitude and phase stability: ± 0.1 dB / ± 2 deg.
- Frequency coverage 75 - 110 GHz.
- Precision waveguide test port WR-10 IEEE 1785.2a (UG-387/UM compatible).
- Lightweight: 1.8 kg (AET) and 1.3 kg (AER).



We required simple and easy-to-use frequency extension systems that enable coherent phase and amplitude measurements. We also required a very high dynamic range and full waveguide bandwidth coverage. All these features, together with high stability and small form factor, make Farran's AET/AER modules a perfect solution for our antenna range measurements.

Senior Antenna Test Engineer, Space Research and Technology Centre

Clarke & Severn Electronics
Ph +612 9482 1944
Email sales@clarke.com.au
www.clarke.com.au
webshop: www.cseonline.com.au



RADIATION PATTERN MEASUREMENTS

- Lightweight and compact - ideal for omni-directional spherical systems and scanners.
- High measurement speed.



GAIN, PHASE AND POLARISATION MEASUREMENTS

- Coherent phase and amplitude measurements.
- High phase and amplitude stability.
- Very high dynamic range.



NEAR- AND FAR-FIELD MEASUREMENTS

- Spherical near- and far-field measurements.
- Far-field measurements of low gain antennas.





Product Specification

System Specification	Unit	Min	Typ	Max
Operating Frequency	GHz	75	-	110
Dynamic Range	dB	110	130	-
Test Port Output Power	dBm	-	+3	-
Magnitude Trace Stability (typ.)	dB	-	±0.1	-
Phase Trace Stability (typ.)	deg	-	±2	-
RF/LO Port Damage Level (nom.)	dBm	+15	-	-
RF Input Frequency	GHz	12.5	-	18.33
RF Multiplier Number (nom.)	-	-	6	-
RF/LO Power Input	dBm	5	-	10
LO Input Frequency	GHz	9.375	-	13.75
LO Harmonic Number (nom.)	-	-	8	-
RF Test Port (nom.)	-	WR-10, IEEE 1785.2a (UG-387/UM compatible)		
RF Test Port VSWR (typ.)	-	-	<1.4:1	-
RF Input VSWR (typ.)	-	-	<1.4:1	-
IF Bandwidth (nom.)	MHz	5	-	1000
RF/LO/IF Ports	-	SMA(F)		
DC Power Requirements (typ.)	-	+12V @ 1.5A		
Dimensions (approx.) AET	mm	230 x 105 x 60		
Dimensions (approx.) AER	mm	170 x 105 x 60		
Weight (approx.) AET	kg	1.8		
Weight (approx.) AER	kg	1.3		
Operating Temperatures (nom.)	°C	0	-	30



SERVICES AVAILABLE

- Technical Support
- Installation and Setup
- Maintenance
- Application Support
- Hardware Support

For more information on any of our products or services please visit our website: www.farraan.com



TECHNICAL SUPPORT

- Technical support provided directly by our knowledgeable and friendly engineers.
- Support for pre- and post-purchase: system configuration, installation and troubleshooting.



PRODUCT INSIGHTS

- For more product insights register at www.farraan.com/customer
- Additional information: test data, CAD drawings and 3D models available.



WARRANTY

- Standard 3 year warranty.
- Up to 5 year warranty optional.

Specification Definitions

Nominal value (nom.) – ensured by design, not tested. **Measured value (min, max)** – expected and warranted product performance obtained from the actual measurements of product sample. **Non-traceable measured value (n. trc. meas.)** – expected product performance obtained from the actual measurements of a product sample by means of using Farraan's own equipment and methods. Traceable only to Farraan laboratory equipment. **Typical data (typ.)** – value that represents the product specification met over 90% of bandwidth or a mean value. **Specifications without limits** – represent the warranted product performance; with values of no or a negligible deviation from the given value and as such have a secondary impact on the product performance.

