


 **Mini-Circuits®**  
Finding New Ways. Setting Higher Standards.



ULTRA SMALL 0805 CERAMIC

# Power Splitter/Combiners



## 3 Way-0° 50Ω

### Features

- Low insertion loss, 1.2 dB typ.
- Excellent amplitude unbalance, 0.2-0.4 dB typ.
- Excellent phase unbalance, 5 deg. typ.
- High isolation, 17-18 dB typ.
- ESD non-sensitive
- Temperature stable LTCC technology
- Wrap around terminations for excellent solderability

**SCG-3-162+**

900-1600 MHz  
for more information

[CLICK HERE](#)

**SCG-3-262+**

1600-2600 MHz  
for more information

[CLICK HERE](#)

**SCG-3-592+**

4400-5900 MHz  
for more information

[CLICK HERE](#)



 **ROGERS CORPORATION**

**CLICK HERE**

for your **ROGERS PCB MATERIAL**

## Visit our WEBSHOP

Clarke & Severn Electronics | Phone: +612 9482 1944 | Email: [sales@clarke.com.au](mailto:sales@clarke.com.au)  
Webshop: [www.cseonline.com.au](http://www.cseonline.com.au) Website: [www.clarke.com.au](http://www.clarke.com.au)

ISO9001:2015 Certified in Feb 2018 View Certificate [HERE](#)