

MINI-CIRCUITS ATTENUATORS - CONNECTORISED - N-TYPE

Clarke & Severn Electronics Ph: +612 9482 1944

www.cseonline.com.au

Attenuators, Coaxial (Type N) • 0.5 - 1.0 Watt • 1 to 20 dB, DC to 6000 MHz

Model Number	Frequency Range (MHz)		Attenuation (dB)					VSWR (:1)					Power (W)
			Nom.	Flatness				DC-3000		3000-4500		4500-6000	
	DC-3000	3000-4500		4500-6000	DC-6000	Typ.	Max.	Typ.	Max.	Typ.			
											Low	High	
UNAT-1+	DC	6000	1	0.2	0.15	0.1	0.45	1.05	1.2	1.1	1.43	1.4	1
UNAT-2+	DC	6000	2	0.2	0.25	0.15	0.5	1.07	1.2	1.22	1.43	1.5	1
UNAT-3+	DC	6000	3	0.2	0.1	0.1	0.35	1.05	1.2	1.22	1.43	1.5	1
UNAT-4+	DC	6000	4	0.15	0.15	0.1	0.4	1.05	1.2	1.1	1.43	1.5	1
UNAT-5+	DC	6000	5	0.15	0.15	0.1	0.35	1.05	1.2	1.1	1.43	1.5	1
UNAT-6+	DC	6000	6	0.15	0.15	0.15	0.4	1.05	1.2	1.2	1.43	1.5	1
UNAT-7+	DC	6000	7	0.1	0.1	0.15	0.2	1.05	1.2	1.1	1.43	1.5	1
UNAT-8+	DC	6000	8	0.1	0.1	0.1	0.1	1.05	1.2	1.1	1.43	1.5	1
UNAT-9+	DC	6000	9	0.15	0.1	0.1	0.15	1.05	1.2	1.1	1.43	1.5	1
UNAT-10+	DC	6000	10	0.1	0.2	0.2	0.4	1.15	1.35	1.2	1.5	1.5	1
UNAT-12+	DC	6000	12	0.15	0.2	0.15	0.35	1.15	1.25	1.2	1.8	1.8	1
UNAT-15+	DC	6000	15	0.2	0.35	0.2	0.6	1.15	1.43	1.2	1.8	1.7	1
UNAT-20+	DC	6000	20	0.25	0.45	0.4	0.75	1.15	1.25	1.2	1.43	1.5	0.5
UNAT-30+	DC	6000	30	1.2	0.7	0.4	2.3	1.04	1.25	1.07	1.25	1.1	0.5