

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
147	40	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Molded black plastic	11 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	7.14mm
151	60	3	Solder lug	Molded black plastic	12B		7.14mm
147	70	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	9.65mm
151	90	3	Solder lug	Shielded	12B		9.53mm
155	133	3	Solder Lug & Cable Clamp	Nickel-plated copper alloy.	298	Sleeve terminal has cable clamp. Similar to Switchcraft Number 131 Extension-Jax	7.54mm
147	160	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	7.14mm
147	170	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	6.35mm
148	172	2	Screw. (Replacement Screw Part No. P-1011-3) 2 Required.	Shielded - machined Nickel-plated copper alloy. Tubular insulator inside handle.	11		6.35mm
152	173	2		Molded black plastic	11	Flex Relief: U-Clamp	7.11mm
152	175	2		Copper Alloy	11	Flex Relief: None	7.11mm
152	178	2		Molded black plastic	11	Flex Relief: None	7.11mm
152	179	2		Molded red plastic	11	Flex Relief: None	7.11mm
148	181	2	Solder Lug & Cable Clamp	Shielded - machined Nickel-plated copper alloy. Tubular insulator inside handle.	11		6.35mm
148	182	2	Solder Lug & Cable Clamp	Shielded - machined Nickel-plated copper alloy. Tubular insulator inside handle.	11		6.35mm
147	184	2	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11 or Z15J	1/4" Mono 2 Conductor Cable Mount - Solder Lugs, Large .380" Hole	9.65mm
149	187		Solder Lug & Cable Clamp	Die-cast zinc. Satin nickel finish.	11 or Z15J	Cable Relief Bushing diameter. (Inch) .3 to .33 (regular).	7.62-8.38mm
151	190	3	Solder lug	Shielded	12B		9.65mm
153	220	2	Screw	Molded black plastic	11		7.14mm
153	225	2	Screw	Molded red plastic	11		7.14mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
154	226	2	1/4" right-angle commercial plug	Nickel-plated copper alloy.	11, 12A, 111, 112A		7.54mm
153	227	2	Solder lug	Molded black plastic	11		5.33-6.35mm
153	228	2	Solder lug	Shielded. Steel, nickel-plated	11		5.33-6.35mm
153	229	2	Solder lug	Molded red plastic	11		5.33-6.35mm
153	230	3	Screw	Molded black plastic	12B		7.14mm
153	235	3	Screw	Molded red plastic	12B		7.14mm
154	236	3	1/4" right-angle commercial plug	Nickel-plated copper alloy.	12B, 13B, 112B, 113B		7.54mm
153	237	3	Solder	Molded black plastic	12B		6.35mm
153	238	3	Solder lug	Shielded. Steel, nickel-plated	12B		5.33-6.15mm
153	239	3	Solder	Molded red plastic	12B		6.35mm
145	240	2	Screw	Molded black plastic	11	1/4" Mono 2 Conductor Cable Mount Plug, Black Plastic w/Screw Terminals	7.52mm
145	245	2	Screw	Molded red plastic	11	1/4" Mono 2 Conductor Cable Mount Plug, Red Plastic w/Screw Terminals	7.54mm
145	250	2	Solder Lug & Cable Clamp	Molded black plastic	11	1/4" Mono 2 Conductor Cable Mount Plug, Black Plastic w/Solder Lug & Cable Clamp	7.54mm
145	255	2	Solder Lug & Cable Clamp	Molded red plastic	11	1/4" Mono 2 Conductor Cable Mount Plug, Red Plastic Handle w/Solder Lug & Cable Clamp	7.54mm
145	260	3	Screw	Molded black plastic	12B	1/4" Stereo 3 Conductor Cable Mount Plug, Black Plastic w/Screw Terminals (No Cable Clamp)	7.54mm
145	267	3	Solder Lug & Cable Clamp	Molded black plastic	12B		7.54mm
145	269	3	Solder Lug & Cable Clamp	Molded red plastic	12B		7.54mm
145	270	2	Screw	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	1/4" Mono 2 Conductor Cable Mount Plug, Nickel Metal Handle w/Screw Terminals (No Cable Clamp)	7.52mm
146	270	2	Screw terminals. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.52mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
145	280	2	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	1/4" Mono 2 Conductor Cable Mount Plug, Nickel Metal Handle w/Solder Lugs & Cable Clamp	7.54mm
146	280	2	Solder lug & cable clamp. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
145	281	2	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	Same as Switchcraft# 280 except unassembled	7.54mm
146	281	2	Solder lug & cable clamp. Shielded handle. Unassembled	nickel-plated zinc (tubular insulator inside handle). Plain handle.	11	Plugs have 1/4" finger diameter unless otherwise specified. Same as Switchcraft# 280 except unassembled	7.54mm
155	282	2	Solder Lug & Cable Clamp	Nickel-plated copper alloy.	12A	Similar to Switchcraft Number 297 Littell-Plug except with couplong ring.	6.7mm
145	285	2	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	Same as Switchcraft# 280 except w/Larger Cable clamp & unassembled	7.54mm
146	285	2	Solder lug & cable clamp. Shielded handle. Unassembled. Larger cable clamp accommodates larger cables.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	11	Plugs have 1/4" finger diameter unless otherwise specified. Same as Switchcraft# 280 except unassembled	7.54mm
145	288	2	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	1/4" Mono 2 Conductor Cable Mount Plug, Nickel Metal Handle w/Solder Lugs & Cable Clamp (wide insulator between tip and sleeve allows use of two conductor plug in 3 conductor jack without shorting)	7.54mm
146	288	2	Solder lug & cable clamp. Shielded handle. Wide insulator between tip and sleeve makes possible use as a 2-conductor plug in 3-conductor jack without shorting.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
145	290	3	Screw	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	12B		7.54mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
146	290	3	Screw terminals. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	12B	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
145	297	3	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	12B		7.54mm
146	297	3	Solder lug & cable clamp. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	12B	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
146	298	3	Solder lug & cable clamp. Shielded handle. Locking feature.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	12B, 134	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
155	298	3	Solder Lug & Cable Clamp	Nickel-plated copper alloy.	12B, 133	Similar to Switchcraft Number 297 Littell-Plug except with couplong ring.	7.54mm
150	299			Nickel-plated copper alloy.	Z15J	Maximum Cable Size: .290" diameter	7.37mm
148	350	2	Solder Lug.	Molded black plastic	11		7.54mm
148	380	2	Solder Lug.	Shielded: Nickel-plated copper alloy.	11	1/4" Mono 2 Conductor Cable Mount Plug, 1" Long Nickel Metal Handle w/Solder Lugs (No Cable Clamp)	7.54mm
141	411	2	Screw	Thermoplastic on 411, 412, 414 and 415, per MIL-P-22985, Type II, Class 4. Molded black thermoset plastic per MIL-M-14F.	MT388	Provision for internal cord clamp (not included)	7.92mm
141	412	2	Screw	Thermoplastic on 411, 412, 414 and 415, per MIL-P-22985, Type II, Class 4. Molded black thermoset plastic per MIL-M-14F.	MT388	MILPJ289. Similar to WECO289B	7.1mm
141	414	3	Screw	Thermoplastic on 411, 412, 414 and 415, per MIL-P-22985, Type II, Class 4. Molded black thermoset plastic per MIL-M-14F.	MT389	6-circuit plug, 2 electrically-independent 3 conductor fingers, .25" fingers. Provision for internal cord clamp (not included). Similar to WECO338A. 425A-3	7.9mm
141	415	3	Screw	Thermoplastic on 411, 412, 414 and 415, per MIL-P-22985, Type II, Class 4. Molded black thermoset plastic per MIL-M-14F.	MT332B & 1, MT342B	6-circuit plug, 2 electrically-independent 3 conductor fingers, one .25" finger, one .206" finger. Provision for internal cord clamp (not included)	7.9mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
138	420	2	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black.	MT331	Similar to WECO-347D	
138	425	2	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black.	MT331		
138	430	2	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black.	820		6.35mm
138	440	2	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black	MT331		7.14mm
138	445	2	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black/Red.	MT331		7.14mm
138	482	3	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black/Red.	MT334B		6.71mm
138	483	3	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black.	MT334B	Similar to WECO-309.	7.65mm
146	570	2	Screw terminals. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.52mm
146	580	2	Solder lug & cable clamp. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
146	581	2	Solder lug & cable clamp. Shielded handle. Unassembled	nickel-plated zinc (tubular insulator inside handle). Logo handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
146	585	2	Solder lug & cable clamp. Shielded handle. Unassembled. Larger cable clamp accommodates larger cables.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	11	Plugs have 1/4" finger diameter unless otherwise specified. Same as Switchcraft# 580 except w/Larger Cable clamp & unassembled	7.54mm
146	588	2	Solder lug & cable clamp. Shielded handle. Wide insulator between tip and sleeve makes possible use as a 2-conductor plug in 3-conductor jack without shorting.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
146	590	3	Screw terminals. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	12B	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
146	597	3	Solder lug & cable clamp. Shielded handle.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	12B	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
146	598	3	Solder lug & cable clamp. Shielded handle. Locking feature.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	12B, 133	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
157	740	2	Screw	Molded black plastic	41, 125, 42A, 43A, 142A, PC142A		9.65mm
157	745	2	Screw	Molded red plastic	41, 125, 42A, 43A, 142A, PC142A		9.65mm
157	750	2	Solder Lug & Cable Clamp	Molded black plastic	41, 125, 42A, 43A, 142A, PC142A		9.65mm
157	755	2	Solder Lug & Cable Clamp	Molded red plastic	41, 125, 42A, 43A, 142A, PC142A		9.65mm
157	770	2	Screw	Shielded	41, 125, 42A, 43A, 142A, PC142A		9.65mm
157	780	2	Solder Lug & Cable Clamp	Shielded	41, 125, 42A, 43A, 142A, PC142A		9.65mm
142	820	2	Screw	Molded black plastic	430		6.35mm
152	174S	2		Copper Alloy	11	Flex Relief: Spring	7.11mm
152	176S	2		Molded black plastic	11	Flex Relief: Spring	7.11mm
152	177S	2		Molded red plastic	11	Flex Relief: Spring	7.11mm
147	182QB	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	12 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	6.35mm
147	182QD	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	13 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	6.35mm
147	184L	2	Solder Lug & Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11 or Z15J	1/4" Mono 2 Conductor Cable Mount - Solder Lugs, Large .451" Hole	11.51mm
149	187B		Solder Lug & Cable Clamp	Die-cast zinc. Black finish.	11 or Z15J	Cable Relief Bushing diameter. (Inch) .3 to .33 (regular).	7.62-8.38mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
149	187BD		Solder Lug & Cable Clamp	Die-cast zinc. Black finish.	11 or Z15J	Cable Relief Bushing diameter. (Inch) .2 to .30 (small)	5.08-7.63mm
149	187BL		Solder Lug & Cable Clamp	Die-cast zinc. Black finish.	11 or Z15J	Cable Relief Bushing diameter. (Inch) .33 to .355 (large)	8.38-9.02mm
149	187D		Solder Lug & Cable Clamp	Die-cast zinc. Satin nickel finish.	11 or Z15J	Cable Relief Bushing diameter. (Inch) .2 to .30 (small)	5.08-7.62mm
149	187L		Solder Lug & Cable Clamp	Die-cast zinc. Satin nickel finish.	11 or Z15J	Cable Relief Bushing diameter. (Inch) .33 to .355 (large)	8.38-9.02mm
151	190A	3	Solder lug	Shielded	12B		6.35mm
151	190B	3	Solder lug	Shielded	12B		6.35mm
151	190BL	3	Solder lug	Shielded	12B		6.35mm
145	285L	2		Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	Same as Switchcraft# 280 except w/Larger Cable clamp, .375" Rear Hole in Handle and Unassembled	9.53mm
148	2P-1216	2	Solder Lug.		11		N/A
145	2P1248	3	Solder Lug & Cable Clamp	Without handle	12B		N/A
147	2P1251	2	Screw. (Replacement Screw Part No. P10013) 2 Required.	Without handle	11 or Z15J	General purpose plug fits all standard jacks. Available in both 2- and 3-conductor types.	N/A
145	2P1298	2	Solder Lug & Cable Clamp	Without handle	11		N/A
157	2P1384	2	Solder Lug & Cable Clamp	Less handle	41, 125, 42A, 43A, 142A, PC142A		N/A
145	2P1495	2	Screw	Without handle	11		N/A
153	2P1509	2	Screw	Less handle	11		N/A
143	2P2003	3	Screw	None			N/A
156	35HDBAU		Plug Finger: Gold	Black plastic.	35RS Series. 35P		7.37mm
156	35HDBAUS		Plug Finger: Gold	Black plastic.	35RS Series. 35P	0.175"handle opening	4.45mm
156	35HDBN		Plug Finger: Nickel	Black plastic.	35RS Series. 35P		7.37mm
156	35HDBNS		Plug Finger: Nickel	Black plastic.	35RS Series. 35P	0.175"handle opening	4.45mm
156	35HDNAU		Plug Finger: Gold	Nickel.	35RS Series. 35P		7.37mm
156	35HDNAUS		Plug Finger: Gold	Nickel.	35RS Series. 35P	0.175"handle opening	4.45mm
156	35HDNN		Plug Finger: Nickel	Nickel.	35RS Series. 35P		7.37mm
156	35HDNNS		Plug Finger: Nickel	Nickel.	35RS Series. 35P	0.175"handle opening	4.45mm
156	35HDRAAU		Plug Finger: Gold	Nickel.	35RS Series. 35P	Right angle	7.37mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
156	35HDRABAU		Plug Finger: Gold	Black plastic.	35RS Series. 35P	Right angle	7.37mm
156	35HDRANN		Plug Finger: Nickel	Nickel.	35RS Series. 35P	Right angle	7.37mm
138	480 (.206")	3	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1. Black.	MT342B		7.54mm
140	482N	3	Screw	Molded Red plastic			5.06mm
140	482NC	3	Cable Clamp	Shielded. Red, metal finish.			5.06mm
140	482NCP	3	Cable Clamp	Molded Red plastic			5.06mm
140	483N	3	Screw	Molded Black plastic			7.60mm
140	483NC	3	Cable Clamp	Shielded. Black metal finish.			7.60mm
140	483NCP	3	Cable Clamp	Molded black plastic.			7.60mm
	483Z	3	Screw	Molded black plastic.			6.71mm
138	484 (.206")	3	Tinned cooper alloy	Thermoplastic, per MIL-P-22985, Type II, Class 1.	MT342B		6.813mm
140	485NC	3	Cable Clamp	Shielded. Nickel finish.			
145	C240	2	Screw with Cable Clamp	Molded black plastic	11	1/4" Mono 2 Conductor Cable Mount Plug, Black Plastic w/Screw Terminals	7.54mm
145	C245	2	Screw with Cable Clamp	Molded red plastic	11	1/4" Mono 2 Conductor Cable Mount Plug, Red Plastic w/Screw Terminals	7.54mm
145	C270	2	Screw with Cable Clamp	Shielded - machined nickel-plated copper alloy. Tubular insulator inside handle.	11	1/4" Mono 2 Conductor Cable Mount Plug, Nickel Metal Handle w/Screw Terminals & Cable Clamp	7.52mm
153	S230	3	Screw	Molded black plastic	S12B		7.14mm
151	S250	2	Solder Lug & Cable Clamp	Molded black plastic	S11		7.54mm
151	S260	3	Screw. (Replacement Screw Part No. P10292) 2 Required.	Molded black plastic	S12B		7.52mm
151	S267	3	Solder Lug & Cable Clamp	Molded black plastic	S12B		7.54mm
146	S280	2	Solder lug & cable clamp. Shielded handle. Plug finger has .206" diameter.	nickel-plated zinc (tubular insulator inside handle). Plain handle.	S11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
151	S280	2	Solder Lug & Cable Clamp	Shielded	S11		7.54mm
146	S580	2	Solder lug & cable clamp. Shielded handle. Plug finger has .206" diameter.	nickel-plated zinc (tubular insulator inside handle). Logo handle.	S11	Plugs have 1/4" finger diameter unless otherwise specified.	7.54mm
143	TT251	2	Screw	Molded black plastic			7.9mm
143	TT252	2	Screw	Molded red plastic			7.9mm

Complete Guide to Switchcraft Plugs and Jacks

Plug Part Numbers

Engineering Design Guide Fourth Edition Page Number	Part Number - Plug	Conductors	Description/Terminal	Handles	Typical Mating Jack	Notes	Max Cable OD
143	TT253	3	Screw	Molded black plastic		Mil-typeM642/13-1	7.9mm
143	TT253N	3	Screw	Molded black plastic		Nickel-plated plug	7.9mm
143	TT253NC	3	Solder	Molded black plastic		Nickel-plated plug, tinned solder terminals	7.9mm
143	TT254	3	Screw	Molded red plastic		Mil-typeM642/13-2	7.9mm
143	TT254N	3	Screw	Molded red plastic		Nickel-plated plug	7.9mm
143	TT254NC	3	Solder	Molded red plastic		Nickel-plated plug, tinned solder terminals	7.9mm
144	TT261	2	Screw	Molded black plastic	TT31		3.97mm
144	TT263	3	Screw	Molded black plastic	TT32B		3.97mm